

Royal Enfield Meteor 300 Mile Maintenance

300 mile maintenance		Meteor
1	Change engine oil and filter, clean oil strainer	
2	Inspect and adjust valve clearance In .08mm Ex .18mm	
3	Inspect spark plug wires	
4	Inspect rubber hose air filter to throttle body	
5	Inspect rubber hose inlet manifold/adaptor	
6	Inspect rubber hose emission related components	
7	Clean air filter element	
8	Inspect vent pipe under air filter box	
9	Inspect secondary air injection hose	
10	Adjust throttle cable free play	
11	Adjust clutch cable freeplay	
12	Lubricate hand lever pivot points	
13	Inspect brake pads/Calipers Front and Rear	
14	Inspect brake fluid level/condition	
15	Lubricate brake lever and gear shifter pivot points	
16	Inspect brake lines/banjo bolt fittings	
17	Inspect front forks for leakage	
18	Inspect steering head movement	
19	Clean lube and adjust rear drive chain	
20	Inspect spoke tightness/rim runout	
21	Clean and tighten battery terminal connections	
22	Inspect side stand switch	
23	Inspect tire condition/wear level	
24	Lubricate side stand/center stand	
25	Lubricate foot rest pivots	
26	Inspect critical fasteners for tightness	
27	Test ride	
Thank you from your Royal Enfield Technician_____		

Royal Enfield Meteor 6000 Mile Maintenance

6000 mile maintenance		Meteor
1	Change engine oil and filter, clean oil strainer	
2	Inspect and adjust valve clearance In .08mm Ex .18mm	
3	Check and adjust spark plug	
4	Inspect spark plug wires	
5	Inspect rubber hose air filter to throttle body	
6	Inspect rubber hose inlet manifold/adapter	
7	Inspect rubber hose emission related components	
8	Clean/replace air filter element	
9	Inspect vent pipe under air filter box	
10	Inspect secondary air injection hose	
11	Adjust throttle cable free play	
12	Adjust clutch cable freeplay	
13	Lubricate hand lever pivot points	
14	Inspect brake pads/Calipers Front and Rear	
15	Inspect brake fluid level/condition	
16	Lubricate brake lever and gear shifter pivot points	
17	Inspect brake lines/banjo bolt fittings	
18	Inspect front forks for leakage	
19	Inspect steering head movement	
20	Clean lube and adjust rear drive chain	
21	Inspect spoke tightness/rim runout	
22	Clean and tighten battery terminal connections	
23	Inspect side stand switch	
24	Inspect tire condition/wear level	
25	Lubricate side stand/center stand	
26	Lubricate foot rest pivots	
27	Inspect critical fasteners for tightness	
28	Test ride	

Thank you from your Royal Enfield Technician _____

Royal Enfield Meteor 12000 Mile Maintenance

12000 mile maintenance		Meteor
1	Change engine oil and filter, clean oil strainer	
2	Inspect and adjust valve clearance In .08mm Ex .18mm	
3	Replace spark plug	
4	Inspect spark plug wires	
5	Inspect rubber hose air filter to throttle body	
6	Inspect rubber hose inlet manifold/adapter	
7	Inspect rubber hose emission related components	
8	Replace air filter element	
9	Inspect vent pipe under air filter box	
10	Inspect secondary air injection hose	
11	Adjust throttle cable free play	
12	Adjust clutch cable freeplay	
13	Lubricate hand lever pivot points	
14	Inspect brake pads/Calipers Front and Rear	
15	Replace Brake fluid	
16	Lubricate brake lever and gear shifter pivot points	
17	Inspect brake lines/banjo bolt fittings	
18	Replace front fork oil	
19	Inspect steering head movement	
20	Clean lube and adjust rear drive chain	
21	Inspect spoke tightness/rim runout	
22	Inspect/replace rear wheel cush rubbers	
23	Clean and tighten battery terminal connections/ground connections	
24	Inspect side stand switch	
25	Inspect tire condition/wear level	
26	Lubricate side stand/center stand/foot rest pivots	
27	Inspect critical fasteners for tightness	
28	Test ride	

Thank you from your Royal Enfield Technician _____

Royal Enfield Twin 300 Mile Maintenance

300 mile maintenance		GT/INT
1	Change engine oil and filter, clean magnetic drain plugs	
2	Inspect and adjust valve clearance In .08mm Ex .18mm	
3	Inspect spark plug	
4	Inspect spark plug wires	
5	Inspect rubber hose air filter to throttle body	
6	Inspect rubber hose inlet manifold/adaptor	
7	Inspect rubber hose emission related components	
8	Clean air filter element	
9	Inspect vent pipe under air filter box	
10	Inspect secondary air hose	
11	Adjust throttle cable free play	
12	Adjust clutch cable freeplay	
13	Lubricate hand lever pivot points	
14	Inspect brake pads/Calipers Front and Rear	
15	Inspect brake fluid level/condition	
16	Lubricate brake lever and gear shifter pivot points	
17	Inspect brake lines/banjo bolt fittings	
18	Inspect front forks for leakage	
19	Inspect steering head movement	
20	Clean lube and adjust rear drive chain	
21	Inspect spoke tightness/rim runout	
22	Clean and tighten battery terminal connections	
23	Inspect tire condition/wear level	
24	Lubricate side stand/center stand	
25	Lubricate foot rest pivots	
26	Inspect critical fasteners for tightness	
27	Test ride	

Thank you from your Royal Enfield Technician _____

Royal Enfield Twin 3000 Mile Maintenance

3000 mile maintenance		GT/INT
1	Inspect spark plug	
2	Inspect spark plug wires	
3	Inspect rubber hose air filter to throttle body	
4	Inspect rubber hose inlet manifold/adapter	
5	Inspect rubber hose emission related components	
6	Clean air filter element	
7	Inspect vent pipe under air filter box	
8	Inspect secondary air hose	
9	Adjust throttle cable free play	
10	Adjust clutch cable freeplay	
11	Lubricate hand lever pivot points	
12	Inspect brake pads/Calipers Front and Rear	
13	Inspect brake fluid level/condition	
14	Lubricate brake lever and gear shifter pivot points	
15	Inspect brake lines/banjo bolt fittings	
16	Inspect front forks for leakage	
17	Inspect steering head movement	
18	Clean lube and adjust rear drive chain	
19	Inspect spoke tightness/rim runout	
20	Clean and tighten battery terminal connections	
21	Inspect tire condition/wear level	
22	Lubricate side stand/center stand	
23	Lubricate foot rest pivots	
24	Inspect critical fasteners for tightness	
25	Test ride	

Thank you from your Royal Enfield Technician _____

Royal Enfield Twin 6000 Mile Maintenance

6000 mile maintenance		GT/INT
1	Change engine oil and filter, clean magnetic drain plugs	
2	Inspect and adjust valve clearance In .08mm Ex .18mm	
3	Inspect spark plug	
4	Inspect spark plug wires	
5	Inspect rubber hose air filter to throttle body	
6	Inspect rubber hose inlet manifold/adapter	
7	Inspect rubber hose emission related components	
8	Replace air filter element	
9	Inspect vent pipe under air filter box	
10	Inspect secondary air hose	
11	Adjust throttle cable free play	
12	Adjust clutch cable freeplay	
13	Lubricate hand lever pivot points	
14	Inspect brake pads/Calipers Front and Rear	
15	Inspect brake fluid level/condition	
16	Lubricate brake lever and gear shifter pivot points	
17	Inspect brake lines/banjo bolt fittings	
18	Inspect front forks for leakage	
19	Inspect steering head movement	
20	Clean lube and adjust rear drive chain	
21	Inspect spoke tightness/rim runout	
22	Clean and tighten battery terminal connections	
23	Inspect tire condition/wear level	
24	Lubricate side stand/center stand	
25	Lubricate foot rest pivots	
26	Inspect critical fasteners for tightness	
27	Inspect ground terminals/tighten	
28	Test ride	

Thank you from your Royal Enfield Technician _____

Royal Enfield Twin 9000 Mile Maintenance

9000 mile maintenance		GT/INT
1	Inspect spark plug	
2	Inspect spark plug wires	
3	Inspect rubber hose air filter to throttle body	
4	Inspect rubber hose inlet manifold/adapter	
5	Inspect rubber hose emission related components	
6	Clean air filter element	
7	Inspect vent pipe under air filter box	
8	Inspect secondary air hose	
9	Adjust throttle cable free play	
10	Adjust clutch cable freeplay	
11	Lubricate hand lever pivot points	
12	Inspect brake pads/Calipers Front and Rear	
13	Inspect brake fluid level/condition	
14	Lubricate brake lever and gear shifter pivot points	
15	Inspect brake lines/banjo bolt fittings	
16	Inspect front forks for leakage	
17	Inspect steering head movement	
18	Clean lube and adjust rear drive chain	
19	Inspect spoke tightness/rim runout	
20	Clean and tighten battery terminal connections	
21	Inspect tire condition/wear level	
22	Lubricate side stand/center stand	
23	Lubricate foot rest pivots	
24	Inspect critical fasteners for tightness	
25	Test ride	

Thank you from your Royal Enfield Technician _____

Royal Enfield Twin 12000 Mile Maintenance

	12000 mile maintenance	GT/INT
1	Change engine oil and filter, clean magnetic drain plugs	
2	Inspect and adjust valve clearance In .08mm Ex .18mm	
3	Replace spark plug	
4	Inspect spark plug wires	
5	Inspect rubber hose air filter to throttle body	
6	Inspect rubber hose inlet manifold/adapter	
7	Inspect rubber hose emission related components	
8	Replace fuel filter	
9	Replace air filter element	
10	Inspect vent pipe under air filter box	
11	Inspect secondary air hose	
12	Adjust throttle cable free play	
13	Adjust clutch cable freeplay	
14	Lubricate hand lever pivot points	
15	Inspect brake pads/Calipers Front and Rear	
16	Replace brake fluid	
17	Lubricate brake lever and gear shifter pivot points	
18	Inspect brake lines/banjo bolt fittings	
19	Inspect front forks for leakage	
20	Inspect steering head movement	
21	Clean lube and adjust rear drive chain	
22	Inspect spoke tightness/rim runout	
23	Clean and tighten battery terminal connections	
24	Inspect tire condition/wear level	
25	Lubricate side stand/center stand	
26	Lubricate foot rest pivots	
27	Inspect critical fasteners for tightness	
28	Inspect ground terminals/tighten	
29	Test ride	

Thank you from your Royal Enfield Technician _____

Royal Enfield 300 Mile Maintenance

300 mile maintenance		Himalayan
1	Change engine oil and filter, clean magnetic drain plugs	
2	Clean oil strainer in LH crankcase	
3	Inspect and adjust Inlet / Exhaust tappet setting In. .08-.10mm Ex. .23-.25mm	
4	Inspect rubber components on intake	
5	Check and adjust Spark plug	
6	Inspect fuel hoses/injector connection for leaks	
7	Inspect fuel pump screws for tightness	
8	Inspect coil wire	
9	Clean air filter element	
10	Inspect/adjust throttle/clutch cables	
11	Inspect clutch for slippage	
12	Inspect and adjust steering head bearings	
13	Inspect fork oil leakage	
14	Clean battery terminals and tighten battery and ground connections	
15	Inspect front and rear brake fluid	
16	Inspect front and rear brake pads	
17	Inspect hydraulic brake fittings, hoses, Calipers	
18	Inspect tires/adjust air pressure	
19	Check spoke tightness and wheel bearings	
20	Inspect and lube swingarm pivot bearings	
21	Inspect rear suspension linkages	
22	Clean and lube chain (every 600 miles or as needed)	
23	Inspect drive chain and sprockets	
24	Inspect rear wheel cush rubbers	
25	Inspect all critical fasteners	
26	Lube levers, side stand, footrest pivots (every 600 miles or as needed)	
27	Inspect emission related components	
28	Test ride	

Thank you from your Royal Enfield Technician _____

Royal Enfield 3000 Mile Maintenance

3000 mile maintenance		Himalayan
1	Inspect oil level	
2	Inspect and adjust Inlet / Exhaust tappet setting In. .08-.10mm Ex. .23-.25mm	
3	Inspect rubber components on intake	
4	Check and adjust Spark plug	
5	Inspect fuel hoses/injector connection for leaks	
6	Inspect fuel pump screws for tightness	
7	Inspect Coil wires	
8	Clean air filter element	
9	Inspect/adjust throttle/clutch cables	
10	Inspect clutch for slippage	
11	Inspect and adjust steering head bearings	
12	Inspect fork oil leakage	
13	Clean battery terminals and tighten battery and ground connections	
14	Inspect front and rear brake fluid	
15	Inspect front and rear brake pads	
16	Inspect hydraulic brake fittings, hoses, Calipers	
17	Inspect tires/adjust air pressure	
18	Check spoke tightness and wheel bearings	
19	Inspect and lube swingarm pivot bearings	
20	Inspect and lube rear suspension linkages	
21	Clean and lube chain (every 600 miles or as needed)	
22	Inspect drive chain and sprockets	
23	Inspect rear wheel cush rubbers	
24	Inspect all critical fasteners	
25	Lube levers, side stand, footrest pivots (every 600 miles or as needed)	
26	Inspect emission related components	
27	Test ride	

Thank you from your Royal Enfield Technician _____

Royal Enfield 6000 Mile Maintenance

6000 mile maintenance		Himalayan
1	Change engine oil and filter, clean magnetic drain plugs	
2	Clean oil strainer in LH crankcase	
3	Inspect and adjust Inlet / Exhaust tappet setting In. .08-.10mm Ex. .23-.25mm	
4	Inspect or replace rubber components on intake	
5	Inspect oil cooler inlet and outlet pipes	
6	Check and adjust Spark plug	
7	Inspect fuel hoses/injector connection for leaks	
8	Inspect fuel pump screws for tightness	
9	Inspect Coil wires	
10	Inspect or replace air filter element	
11	Inspect/adjust/replace throttle/clutch cables	
12	Inspect clutch for slippage	
13	Inspect or replace fuel pipe	
14	Lube and adjust steering head bearings	
15	Inspect fork oil leakage	
16	Clean battery terminals and tighten battery and ground connections	
17	Inspect or replace front and rear brake fluid	
18	Inspect or replace front and rear brake pads	
19	Inspect hydraulic brake fittings, hoses, Calipers	
20	Inspect tires/adjust air pressure	
21	Check spoke tightness and wheel bearings	
22	Inspect/lube swingarm pivot bearings	
23	Inspect/lube rear suspension linkages	
24	Clean and lube chain every (600 miles or as needed)	
25	Inspect/replace drive chain and sprockets	
26	Inspect/replace rear wheel cush rubbers	
27	Inspect all critical fasteners	
28	Lube levers, side stand, footrest pivots every 600 miles or as needed	
29	Inspect emission related components	
30	Test ride	

Thank you from your Royal Enfield Technician _____

Royal Enfield 9000 Mile Maintenance

9000 mile maintenance		Himalayan
1	Inspect oil level	
2	Inspect and adjust Inlet / Exhaust tappet setting In. .08-.10mm Ex. .23-.25mm	
3	Inspect rubber components on intake	
4	Replace spark plug	
5	Inspect fuel hoses/injector connection for leaks	
6	Inspect fuel pump screws for tightness	
7	Inspect Coil wire	
8	Clean air filter element	
9	Inspect/adjust throttle/clutch cables	
10	Inspect clutch for slippage	
11	Inspect and adjust steering head bearings	
12	Inspect fork oil leakage	
13	Clean battery terminals and tighten battery and ground connections	
14	Inspect front and rear brake fluid	
15	Inspect front and rear brake pads	
16	Inspect hydraulic brake fittings, hoses, Calipers	
17	Inspect tires/adjust air pressure	
18	Check spoke tightness and wheel bearings	
19	Inspect and lube swingarm pivot bearings	
20	Inspect and lube/replace rear suspension linkages	
21	Clean and lube chain (every 600 miles or as needed)	
22	Inspect drive chain and sprockets	
23	Inspect rear wheel cush rubbers	
24	Inspect all critical fasteners	
25	Lube levers, side stand, footrest pivots (every 600 miles or as needed)	
26	Inspect/replace emission related components	
27	Test ride	

Thank you from your Royal Enfield Technician _____